


1	GND
2	VGL
3	VGH
4	VSN
5	VSP
6	VDD
7	VDDOTP
8	STBYB
9	SDA
10	SCL
11	CS
12	GND
13	RXIN3+
14	RXIN3-
15	GND
16	RXIN2+
17	RXIN2-
18	GND
19	RXCLKIN+
20	RXCLKIN-
21	GND
22	RXIN1+
23	RXIN1-
24	GND
25	RXTINO+
26	RXTINO-
27	GND
28	UPDN
29	LEDA
30	LEDK



LED CIRCUIT DIAGRAM:  
If I=40mA Voltage=22.4V

Screen Size:	3.97(inch)	OP Temperature:	-20~+70°C	Backlight Characters:	40mA
View Direction:	Full view	ST Temperature:	-30~+80°C	Luminance + LED:	1000nit (TYP)/14PCS
Grey scale:		Analog Voltage:	3.3V	Driver IC :	HX8273
Display mode:	IPS	Digital Voltage:		Reminder :	

Kingtech Group Co.,Ltd.

Outline	NAME: PV04018H0530S		
VER:A	U: mm	S: 1:1	Date: 20231111
APPROVED	CHECKED	DRAWN	

ROHS must be complied Unspecified tolerance is ±0.25mm